# Index

*Note*: Locators followed by "f" and "t" denote figures and tables in the text

# A

Accumulation charge, 96 ACM model, 13 Acoustic phonon scattering, 331–332 Advanced compact MOSFET, 13 Advanced thermal noise model, 264–265 Ambipolar behavior of TFETs, 345 Atoms, donor and acceptor, 27*f* Auger recombination, 44 Avalanche breakdown voltage, 72 Avalanche current, low-level, 212 Avalanche regime, 141

# B

Back-end process variability, 285 Backward propagation of variance (BPV), 296 Band-bending potential formulation of Poisson's equation, 100 - 103variation of, 107f Bandgap widening, 114 Band-to-band recombination, 41, 41f Band-to-band tunneling (BTBT), 3, 175, 218 Barrier height, <mark>52</mark> Basic model, thermal noise, 264 Berkeley Short Channel IGFET Model (BSIM), 7, 324 first generation of, 7 version 4 (BSIM4), 300t, 301-302, 306t-307t, 423 measured data of nMOSFET, 429-431f parameters used in, 186 temperature dependence of, 208-209 Bipolar junction transistors (BJTs), 1, 371 advanced model, 372 areas of applications, 371

basic features of, 372–374 basic operation, 374 bipolar transistors, 371 compact model, 377-415 components of base charge, 403f Ebers-Moll (EM) model, 4 EM2 BJT model, 385 EM1 model, 371 equivalent circuit of SGP, 413f invention of, 4 lateral, 372 mode of operations, 375-377 operating regimes, 4 parasitic circuit elements, 385 physical effects in, 4 Spice Gummel-Poon (SGP) model, 371-372 summary of compact, 412-415 vertical, 372 very-large-scale-ntegrated (VLSI) circuits, 371 Body effect coefficient, 111, 176 Body factor, 137 Boltzmann constant, 86 distribution, 343, 352 distribution function, 333 Breakdown condition, 72 Breakdown regime, 141 Breakdown voltage, 71-72 avalanche, 72 Brews charge-sheet model, 149 Built-in electric field, formation of, 52f Built-in potential, 52–54 Bulk-charge coefficient, 162 Bulk-charge effect, 201–202 Bulk-charge model, 160–161 Bulk-charge sharing, 183 short channel effect in MOSFETs caused by, 184f Bulk mobility, 33

Bulk resistance, 71 Bulk silicon, carrier mobility in, 32 Buried-halo MOSFET (BH-MOSFET), 309, 310*f* Buried oxide (BOx), 318

# C

CAD, See Circuit computer-aided design (CAD) Capacitance, 3 collector-base junction, 373–374 depletion layer, 73 junction, 73-76 Capacitance model, MOSFET, 226–237 intrinsic charges and capacitances, 226-229 limitations of Meyer model, 236-237 Meyer model, 229–236 Capacitance-voltage (C-V)characteristics, 2, 426 deep depletion, 119-121 high frequency (HF), 119 of ideal MOS capacitor system, 120f low frequency (LF), 115-119, 122f Capacitance-voltage (C–V) model, 274 common multigate, 336-338 independent multigate, 338–340 Carrier density fluctuation model, 266 Carrier generation (G), 39 Carrier injection, 40 Carrier mobility, temperature dependence of, 209 Carrier recombination (R), 39 Centerline process technology, 294 Channel length modulation (CLM), 157, 175, 250 early voltage due to, 204 effect of, 159f Channel region, 132 Charge-based capacitance models, 229 channel charge partition, 239 channel length modulation (CLM), 250 lightly doped drain (LDD), 250 long channel capacitance model, 246-247 long channel charge model, 241-246 Miller effect, 247

short channel capacitance model, 250 short channel charge model, 248–250 Ward-Dutton partition, 239 Charge-based compact models, 7, 12–14 Charge density fluctuation model, 266, 327 Charges location of, 90f types of, 89, 90f Charge-sheet model, 146–150 diffusion component of drain current, 148-150 drain current as function of gate voltage obtained by, 150f drift component of drain current, 147–148 Circuit computer-aided design (CAD), 1, 19, 132, 225, 261, 274, 423 compact model for circuit, 3, 5 conventional process variability modeling, 294-296 DC MOSFET model for, 170 diode equivalent circuit for, 77–78 generate compact device model library, 424f MOSFET model for, 152 nanoscale device technology for, 183 parameters of Level 1 MOSFET model for, 160t usage of compact models in circuit, 16f VLSI devices for, 150 Circuit simulation compact models for, 1–3 compact device models, 2–3 compact interconnect models, 3 CMOS, See Complementary metaloxide-semiconductor (CMOS) CMOS field-effect transistor (CMOSFET) 2D-cross section of ideal advanced, 133f CMOS transistor, 132 Collector-base (CB) junction capacitance, 373-374 Common gate, 318 Common multigate (CMG) *C–V* model, 336–338 structure, 318

Compact device model, general approach data collection, 423-427 data fitting to extract parameters, 427-428 generation of library, 429–435 generation of parameter files, 428 model validation, 436 Compact Modeling Council (CMC), 8 found in, 17 Compact TFET models, 357–367 drain current model, 360-367 threshold voltage model, 358-359 Compensated silicon, 28 Complementary metal-oxidesemiconductor (CMOS), 1, 86, 175, 272, 279, 343, 423 critical sources of variability, 287f estimated threshold voltage variation, 289f green IC technology, 343 integrated circuit (IC), 343 International Technology Roadmap for Semiconductors, 288 IONN versus IONP, 437f, 438–439f line-edge roughness (LER), 287, 290 line-width roughness (LWR), 287 oxide thickness variation (OTV), 287, 290-291 random discrete doping (RDD), 287-290 technology, 131 Complementary TFET (CTFET) technology, 356 Conduction band (CB), 20 Conduction electrons, 20 Conductivity effective mass, 26 Core model, 2, 318–328 drain current model, 325-328 electrostatics, 318–324 Correlated carrier and mobility fluctuation model, 266 Coulomb scattering, 191–192, 331–332 Coupling capacitance, 197 Covalent bond, 20 Crystalline silicon, 19 Current continuity, 140 Current crowding, 332 Current density, 139

Current saturation, 332 Current-voltage (*I–V*) characteristics, 2, 426 bulk resistance, 71 junction breakdown voltage, 71–72 limitations, 67–70 of nMOSFET device, 158*f* relation, 299 temperature dependence of leakage current, 67

# D

DC model for EM1, 377-385 Debye length, 104, 350 Deep depletion, 120 C–V characteristics, 119–121 Deep source-drain (DSD) junctions, 177f Density of states effective mass, 26 Depletion approximation, 55 of pn-junction, 57f Depletion approximation, 105–107 Depletion condition, 97 Depletion layer capacitance, 73 Depletion region, 52 DG-nMOSFET device structure drain current model showing volume inversion, 328f drain current model used to simulate SCE, 330f drain current model, volume inversion in lightly doped, 328f schematic of idealized symmetric common, 319f typical symmetric, 316f DIBL, See Drain-induced barrier lowering (DIBL) Diffusion capacitance, 76–77 effect of, 389-392 Diffusion current, 37 Diffusion of carriers, 36–38, 37f in nonuniformly doped *n*-type semiconductor, 38f Digital Equipment Corporation's (DEC) Alpha chip, 9 Diode, 51 current calculation, 66 model at high-level current, 71f tunnel, 348

DITS, See Drain-induced threshold voltage shift (DITS) Donor atoms, 26 Dopants, 26 Double-gate FET (DG-FET), 320, 323, 333 2D cross-sectional view of channel region, 333f Double-gate FinFET (DG-FinFet), 315-316 Poisson's drift/diffusion equations, 318 Double-gate MOSFET (DG-MOSFET), 314 3D cross section of ideal, 315f energy-band diagrams for, 331f Drain current model, 138–171, 190–209, 325-328, 335-336, 360-367 basic feature of nonzero slope for saturated, 159f charge density model, 327 charge-sheet model, 146-150 current voltage characteristics of nMOSFET device, 154f, 158f diffusion component of, 148-150 drain current formulation, 139–142 drift component of, 147-148 drift-diffusion equation, 325 energy band diagram of nMOSFET device, 142f formulation, 139–144 as function of gate voltage obtained by charge sheet model, 150f Gauss's law, 326 ideal, 361-364  $I_{ds} - V_{ds}$  characteristics of nMOSFET device, 159f I–V characteristics, 327f linear region, 197–200 modeling channel transports using drain MOSFET, 364–366 modeling channel transports using source resistance, 366-367 Pao-Sah model, 144–146 regional, 150-171 saturation region, 200–201 schematic diagram of nMOSFET device, 156f simulate SCE lightly doped DG-nMOSFETs, 330f subthreshold region, 197

Taylor's series expansion, 326 volume inversion lightly doped DG-nMOSFETs, 328, 328f Drain-induced barrier lowering (DIBL), 175 early voltage due to, 204 Drain-induced threshold voltage shift (DITS), 183 Drain voltage, 215 short channel effect in MOSFETs due to, 185f DRAM, See Dynamic random-access memory (DRAM) Drift component of drain, 147 Drift current, 33 Drift-diffusion equation, 325 Drift velocity, 31 of electrons and holes in silicon, 36t parameters for field dependence of, 35t Dynamic model common multigate C–V model, 336-338 independent multigate C-V model, 338-340 large signal, 225 small signal, 225 Dynamic random-access memory (DRAM), 10

# E

Early effect, 371–372, 395–397 Early voltage, 203 forward, 407 inverse, 405 Ebers-Moll (EM) model, 4, 371 Effective channel length (L<sub>eff</sub>), 189–190 width (W<sub>eff</sub>), 189–190 Effective gate voltage, 154 Effective mobility, 191 Effective vertical electric field on MOSFET inversion carriers, 191*f* Electrical confinement (EC), 330 Electrical resistivity, 33–34 Electrical test (ET) data, 295-296 Electric field, 31, 55–58 built-in, 38–39

Electron affinity, 85 Electron drift, 31 current density, 33 Electronic design automation (EDA) tools, 1 Electronic energy level, 90 Electron lifetime, 65 Electrostatics, 318-324, 333-334 Elmore's approach, 275 EM2 BJT model, 385 EM model, See Ebers-Moll (EM) model EM1 model DC model for, 377-385 injection version, 380 transport model, 381 EM2 model, 385 Energy band diagram of semiconductor, 21fEnergy band model, 20-21 Excess carriers, 40 Extrinsic semiconductor, 26–31 energy band diagram representation in, 28 Fermi level in, 28–30 form covalent bonds, 27f

# F

Fermi–Dirac (F–D) distribution functions, 22f Fermi–Dirac statistics, 361 Fermi function, 22 Fick's first law of diffusion, 147, 391, 397 Field-effect transistors (FETs), 314, 343 acoustic phonon scattering, 331–332 common multiple-gate, 318–332 compact modeling of, 3 Coulomb scattering, 331–332 3D cross section of typical multifin, 315f FinFET, 309, 314 independent multiple-gate, 332-336 surface roughness scattering, 331-332 UTB-MOSFETs provide major issues solutions, 314 Fin, 315 First-order drain current model, 153 Fixed corner models, 295–297, 305t, 433

Fixed-oxide charge, 90–91 Fix's first law, 37 Flat band condition, 94 Flat band voltage, 88, 92, 94 total shift in, 92 Flicker noise, 266–273 characteristics of nMOSFET and pMOSFET, 272f Hooge's empirical relation, 266 linear region, 270 model, 266-273 noise spectra of an nMOSFET and a pMOSFET, 273f physical mechanism, 266 physical origin different theories, 266 saturation region, 271 small signal equivalent circuit model of MOSFET, 273f subthreshold region, 271-273 1/f noise, See Flicker noise; Lowfrequency noise Forbidden band, 20 Forbidden gap, 20 Formation of built-in electric field, 52f Forward characteristics of real pn-junction, 68f early voltage ( $V_{AF}$ ), 407 emission coefficient, 406 kneecurrent, 411 Free electrons, 20 Front-end process variability, 285–291 Fully depleted channel device, 345

#### G

Gate current model, 219–220, 221*f* Gate current, tunneling components of, 220 Gate electrode, 132 Gate-induced drain leakage (GIDL), 9, 218 body current model, 218–219 current in nMOSFET device, 218*f* Gate-induced source leakage (GISL), 9, 218 Gate leakage current, 3 Gate over drive voltage, 154 Gate resistance, modeling, 279–282 Gate voltage, 168 Gauss's law, 5, 45, 322 GCA, See Gradual channel approximation (GCA) Generation and recombination in an indirect bandgap semiconductor, 42f GHz applications, MOSFET RF model for. 283 GIDL, See Gate-induced drain leakage (GIDL) GISL, See Gate-induced source leakage (GISL) Global process variability, 286–287, 286f GNR, See Graphene nanoribbons (GNR) Golden die, 426 wafer, 426 Gradual channel approximation (GCA), 136, 318 Graphene nanoribbons (GNR), 357 Green IC technology, 343 Gummel plot, 393, 393f Gummel–Poon (GP) model, 4

# H

Halo doping, 177f, 180 nonuniform lateral channel doping profile due to, 181f High frequency (HF) C–V characteristics, 119 C–V plot, 119 High-level injection, 40, 395–412 Hiroshima University STARC IGFET Model (HiSIM), 149 Hooge's empirical relation, 266 Hot carrier current effect in nMOSFETs, 213f Hot carrier effect in MOSFETs, 210f in nMOSFETs, 213f Hot electrons, 210 Householder's method, 324, 334 HSPICE circuit computer-aided design (CAD), 423

# I

ICs, See Integrated circuits (ICs) Ideal drain current model, 361–364 Ideality factor, 69 Ideal MOSFET device structure, 133f Ihantola–Moll model, 161 Impact ionization, 175 coefficients, 212 Impurities, types of, 26 Indefinite admittance matrix, 238 Independent multigate C–V model, 338–340 FET model, 332-336 Independent multigate (IMG), 318 Indirect bandgap semiconductors, 41f, 42 Indirect recombination process, 42, 43f Induced charge density, variation of, 105f Inductance (L), 3 Integrated circuits (ICs), 251, 286, 343, 371, 424 analysis of, 1 invention of, 1 technology for, work functions of commonly used gate material. 87t transistors, 19 Inter-die process variability, 286 Interface states, 90 Interface-trapped charge, 90 International Technology Roadmap for Semiconductors, 288 Intra-die process variability, 287 Intrinsic capacitance model, 238, 336 Intrinsic energy level, 24 Intrinsic Fermi level, 24, 44 Intrinsic process variability, 285 Intrinsic semiconductors, 23–26 Inverse early voltage, 405 Inversion charge density, 160–161 Inversion condition, 98, 98f Inversion layer quantization, 113f Ionized impurity scattering, 192 IR drop, 3 *I–V* (current-voltage) relation, 299

# J

Junction capacitance, 73–76 of typical *pn*-junction, 75*f* 

#### L

Large-signal model, 77 Lateral BJTs, 372 LDCM, See Location depth corner modeling (LDCM) LDD, See Lightly doped drain (LDD) Leakage current, 70–71 Length Debye, 350 natural, 350 screening, 349-350 LER, See Line–edge roughness (LER) Lightly doped drain (LDD), 214, 250 Linear hybrid- $\pi$  small signal model, 382-385 input resistance, 383-384 output resistance, 384-385 Linear region operation, 154 Line-edge roughness (LER), 287, 290 Line-width roughness (LWR), 287 Local oxidation of silicon (LOCOS) isolation process, 186–187 in CMOS technology, 186f Local process variability, 287, 298–299, 301-303 Location depth corner modeling (LDCM), 296 Long channel capacitance model, 246-247 Long channel charge model, 241–246 accumulation, 246 strong inversion, 241-244 weak inversion, 244-246 Lower limit (LL) values, 294–295 Low field mobility degradation, 332 of inversion carriers in MOSFETs, 193f model, **196** Low-frequency noise, 266 Low-level avalanche current, 212 Low-level injection, 40 LWR, See Line–width roughness (LWR)

### Μ

Majority carrier distribution tails or spillover, 60f Mathiessen's rule, 32 Maxwell–Boltzmann (M–B) distribution functions, 22f Maxwell's field equation, 44 Metal-oxide-semiconductor (MOS) capacitor system, 83, 93*f*, 236 under applied bias, 94–99 applied gate bias  $V_{q}$ , 94f applied gate voltage,  $V_g = 0$ , 87f band bending of, 87f band structure for, 89f basic characteristics of, 114 behavior of, 84 *C–V* characteristics of ideal, 120*f* depletion, 105-107 different regimes of, 105f effect of applied voltage, 96f, 97f, 98f energy band diagram of three separate materials form, 85f equilibrium, 83–94 equilibrium band structure of a *p*-type, 101*f* extrinsic capacitances, 226 individual component of total, 115f intrinsic capacitances, 226 inversion, 107-114 low frequency (LF) C-Vcharacteristics of, 115–119, 122f polysilicon depletion effect in, 122f structure, 114–123 surface potential *versus* gate voltage for, 111f theory, 99-114 two-dimensional (2D) cross section of ideal, 84f Metal-oxide-semiconductor field-effect transistors (MOSFETs), 1, 225, 261, 285, 343, 371, 423 accumulation region, 246 advanced compact, 13 basic features of, 133–134, 134f basic theory of, 132 Boltzmann distribution, 352 bulk-charge effect in, 162 capacitance model, 226–237, 226f

Metal-oxide-semiconductor fieldeffect transistors (MOSFETs), (Continued) characteristics of, 138 characterization of parametric variability, 291–293 charge-based capacitance model, 237 charge-based compact models, 7, 12 - 14compact models for small geometry, 175-221 Complete equivalent circuit, 236f complexities of, 7 2D cross section of, 177f 2D cross section of *n*-channel, 136*f* design theory of, 4 determination of process variabilitysensitive, 298-301 device selection criteria, 425f different components of gate overlap capacitance, 251f double integral model for, 145 drain (d), 131 drain current model, 138–171 effective vertical electric field on, 191f effect of nonuniform channel doping profile on, 178f Elmore's equivalent circuit, 278f flicker characteristics of nMOSFET and pMOSFET, 272f four-terminal of, 132 gain factor of, 153 GIDL current in, 218f history of, 4–7 hot carrier effect in, 210f ideal structure of four-terminal, 133f intrinsic capacitances, 238 *I–V* and *C–V* behavior of, 2  $Log (I_{ds})$  versus  $V_{gs}$  characteristics of, 168f low field mobility of inversion carriers in, 193f measured and simulated tunneling currents in, 220f modeling efective gate resistance for RF analysis, 281f modeling of, 140 narrow channel effect in, 186f noise models, 261–273

noise spectra of nMOSFET and pMOSFET, 273f nonreciprocal effect, 237 nonuniform vertical channel doping profile of, 179f NQS effect, 274–279 operation, 135 output characteristics, 203f output characteristics of, 158f overview of, 132-135 Pao-Sah model for, 145 plots for, 217f pn-junctions, 371 QM effects in, 10 quasistatic operation, 227 for RF analysis, 279f, 283f RF model for GHz applications, 283 schematic circuit element, 227f short channel effect in, 184f, 185f small signal equivalent circuit model, 273f source(s), 131 square law model, 157 subthreshold slope degradation, 329-330 surface potential–based, 7, 9–12 threshold voltage-based, 7-9 threshold voltage model, 135–138 total drain current in, 147 trans-capacitances, 238 transisent and small signal equivalent circuit model, 276f two-dimensional (2D) cross section of, 186f velocity saturation in, 196 VLSI circuits consist of, 3 Metal-oxide-semiconductor (MOS) transistor, evolution of, 6 Mever model limitations, 236–237 simple equivalent circuit, 236f Simulation Program with Integrated Circuit Emphasis (SPICE), 229 strong inversion, 231–233 three lumped capacitances, 229-230 weak inversion, 234-236 Miller effect, 247 Mismatch coefficient, 292 Mismatch modeling, 433–434

Mobile ionic charge, 91 Mobility degradation, 331–332 Mobility fluctuation model, 266 Model card definition of different parameters and functions, 435t generate, 434–435 model usage, 436-437 model validation, 436 Modeling base-width modulation and highlevel injection, 395–412 carrier recombination in depletion regions, 394-395 channel transports using drain mosfet, 364-366 channel transports using source resistance, 366-367 mismatch, 433–434 modeling NQS effect in MOSFET, 275 - 279parasitic circuit elements, 385–392 statistical compact, 297–308 systematic process variability, 430-433 Model parameters for MOS level 1 compact model, 160t Moderate inversion, 149 region, 109, 170-171 Monte Carlo (MC) simulation, 304, 308f statistical modeling, 433 Moore's law, 313 MOS capacitor theory, 136 MOSFETs, See Metal-oxidesemiconductor field-effect transistors (MOSFETs) MOS structure, capacitance of, 114–123 Multigate device structures bulk-multigate, 314–317 UTB-SOI, 317-318 Multigate structure, 315

#### Ν

Narrow channel effect in MOSFETs, 186f Narrow width effect (NWE), 183 Natural length, 350

*N*-channel MOSFETs (nMOSFETs)  $I_{ds} - V_{ds}$  characteristics of, 159f *n*-channel MOSFETs (nMOSFETs), 138, 179 channel hot electrons in, 210f charge distribution in, 206f cross section of, 211f current voltage characteristics of, 158f depletion region widening at drain end of channel of, 161f energy band diagram of, 142f hot carrier current effect in, 213f hot carrier effect in, 213f  $I_{ds}$  versus  $V_{gs}$  characteristics of, 219f induced substrate current *I*<sub>sub</sub> versus gate voltage  $V_{gs}$ , 216f schematic diagram of, 139f, 156f universal mobility behavior of inversion layer electrons in, 193f Negative differential resistance (NDR), 346 NFACTOR, 197 NMOS device characteristics, 427f Noise description, 261 Noise models, MOSFETs, 261–273 flicker noise, 265–273 fundamental sources, 262 thermal noise, 262-265 Nonlinear hybrid- $\pi$  model, 381 Non-quasistatic (NQS) analysis, 255 effect, 3, 261, 274–279 Nonuniform doping effects, 3 npn-BJT transistor, 372, 374 basic Ebers–Moll model for, 378f basic feature of, 373f biasing condition of, 375f components of base charge, 403f equivalent circuit of enhanced vertical, 386f four different regions operation of, 376f Gummel plot, 393, 393f layout of vertical, 374f nonlinear hybrid- $\pi$  EM1 model, <u>382</u>*f* 

npn-BJT transistor (Continued) operation, 375f parasitic series resistances, 387f small signal model, 384f structure for modeling early effect, 396f transport version of Ebers–Moll model, 381f used to derive basic Ebers–Moll model, 378f n-type material, 26 n-type TFET (nTFET), 344, 359 NWE, See Narrow width effect (NWE)

#### 0

One-sided step junction, 59–60 OTV, *See* Oxide thickness variation (OTV) Output characteristics, MOSFET, 203*f* Output resistance (*R*<sub>out</sub>), 202–204 Oxide charges, 89–91 fixed-oxide, 90–91 interface-trapped, 90 mobile ionic, 91 oxide-trapped, 91 Oxide thickness variation (OTV), 287, 290–291 Oxide-trapped charge, 91

# P

Pao-Sah model, 5, 144–146 *p*-channel MOSFETs (pMOSFETs), 160, 179 PDF, See Probability distribution function (PDF) Pelgrom plot, 292, 303 Performance-aware model (PAM) cards, 296 Phonon scattering, 192, 194 Piece-wise multisectional model, 150 Pinched-off channel, 271 Pinch-off voltage, 155 *p-i-n* TFET, 344*f*, 347*f*, 350, 351*f*, 352, 358 *pn*-junction, **51**, **51***f* analysis of, 54 applied bias in, 64f charge condition under depletion approximation, 55f

current equation, 67–70 current voltage characteristics of, 67f depletion approximation of, 57f diode, 51 distribution of carriers n-region of, 64f dynamic behavior, 73–77 energy band diagram of, 53f equations, 60–65 in equilibrium, 59f equivalent circuit for, 78f under external bias, 58–60, 59f features of, 51–53 forward characteristics of real, 68f I–V characteristics of, 65–72, 67f potential, 55–58 reverse characteristics of real, 70f reverse (or leakage) current, 71 small signal behavior of, 77 types of stored charge in, 73 pnp-BJT transistor, 372 Pocket doping, nonuniform lateral channel doping profile due to, 181f Point swing, 354 Poisson-carrier transport (core CMG model) drain current model, 325-328 electrostatics, 318-324 Poisson's drift/diffusion equations, 318, 320, 333 Poisson's equation, 5, 14, 44–45 formulation of, 100–103 Polysilicon gate depletion, 205–208 Power spectral density (PSD), 262 Probability distribution function (PDF), 304 PSD, See Power spectral density (PSD) *p*-type TFET (pTFET), 344, 356

# Q

Quantum mechanical effects (QMEs), 3, 330–331 Quantum mechanics (QM), 20, 113–114 Quasi-Fermi level, 48, 269 Quasistatic (QS) assumption, 225, 261 two-dimensional (2D) numerical simulation, 274 Quasistatic model, 228, 254–255

#### R

Radio frequency (RF), 1, 261 applications, modeling parasitic elements for, 279-283 Random discrete doping (RDD), 287-290, 299, 308-309, 314-315 Random process variability, 287 RDD, See Random discrete doping (RDD) Recombination centers, 42 Regional drain current model, 150–171 bulk-charge model, 160–161 core model, 152-160 limitations, 169-171 square root approximation of bulkcharge model, 161-163 subthreshold region, 163-169 Resistance bulk, 71 energy losses in, 3 series, 71f, 332 sheet, 34-35 Reverse characteristics of real pn-junction, 70f Reverse SCE (RSCE), 15

# S

Saturation drain current ( $I_{dsat}$ ), 155 Saturation velocity, temperature dependence of, 209 Saturation voltage ( $V_{dsa}$ ), 155 SC, See Structural confinement (SC) Scaling rule, 316–317 SCBE, See Substrate current-induced body effect (SCBE) Schematic 2D cross section of *n*-channel MOSFET, 136f Schematic diagram of *n*MOSFET device, 139*f*, 156*f* Schichmann and Hodges model, 6 Schrödinger–Poisson approach, 331 Screening length, 349-350 S/D (source-drain) parasitic series resistance, 205 temperature dependence of, 209 Semiconductor bandgap in, 41f carrier transport in, 31–39

current continuity in, 50f dynamic characteristics of, 139-140 effect of band bending on, 93–94 electrical properties of, 21 energy band diagram of, 21f equations, 44–51 Fermi–Dirac (F–D) distribution functions, 22f Fermi level in degenerately doped, 30 - 31field distributions in, 50 indirect bandgap, 41f, 42 induced charge in, 107 industry, 287 Maxwell-Boltzmann (M-B) distribution functions, 22f nonuniformly doped, 38–39 physics, 19-20 resistivity of, 33 Series resistance, 71f, 332 S-factor, 168 Shallow trench isolation (STI), 132, 133f, 187 Sheet resistance, 34–35 Shockley–Read–Hall (SRH), 43 theory of generation and recombination, 68 Short channel capacitance model, 250 Short channel charge model, 248–250 Short channel effects (SCEs), 3, 183, 313, 329-330 Silicon effective mass ratio for, 26t electron and hole mobilities in, 32f Poisson's equation for, 45 surface and bulk impact ionization coefficients in, 213t Silicon dioxide (SiO<sub>2</sub>), 83 energy band diagram for, 85f Silicon-on-insulator (SOI), 9, 313, 315, 317 Simulation Program with Integrated Circuit Emphasis (SPICE), 4, 153, 229 Level 1 model, 160 Simulation Program with Integrated Circuit Emphasis (SPICE2) model, 161, 264 Small signal dynamic model, 225 Smart cut, 317

Source-drain extensions (SDE), 313 regions, 176, 177f Source-drain (S/D) *pn*-junction capacitance model drain-body junction diode, 257–258 source-body pn-junction diode, 256-257 Spice Gummel-Poon (SGP) model, 371-372 SP model, 11 features of, 12 Square law model, 157 Square root approximation, 162 of bulk-charge model, 161–163 SRAM, See Static random access memory (SRAM) Static random access memory (SRAM), 285, 291 Statistical compact modeling, 297-308, 433 BSIM4 compact model parameters, 300t process variability-aware VLSI circuit design, 297f Statistical corner models, 296 Statistical model library, 426 STI, See Shallow trench isolation (STI) Strong inversion, 137 regime, 98, 110 region, 5 Structural confinement (SC), 331 STT, See Surface tunnel transistor (STT) Substrate current-induced body effect (SCBE), 201 early voltage due to, 204 Substrate current model, 210–221 Substrate network, modeling, 282–283 Subthreshold conduction, 167 current, 164 region conduction, 169 slope, 168, 197 slope degradation, 329–330 swing, 353–355 Surface and bulk impact ionization coefficients in silicon, 213t Surface mobility, 33 Surface potential ( $\phi_s$ ), 5 based compact MOSFET model, 9-12 Surface potential–based, 7, 9–12 Surface potential equation (SPE), 324 Surface roughness (SR), 290, 331–332 Surface states, 90 Surface tunnel transistor (STT), 346 Systematic process variability, 285, 430–433

#### Т

Taylor's series expansion, 326 Technology CAD (TCAD) environment, 3 Thermal energy (kT), 25, 36 Thermal G–R process, 40f Thermal noise, 262–265 advanced thermal noise model, 264-265 basic model, 264 equivalent circuit for thermal noise of resistor, 263f models, 263-265 physical mechanism, 262–263 Threshold voltage  $(V_{th})$ , 5, 111, 132, 150 based compact MOSFET model, 7–9 Threshold voltage-based, 7-9 Threshold voltage model, 175–190, 358-359 effect of nonuniform channel doping on, 176–183 for nonuniform lateral channel doping profile, 180–183 for nonuniform vertical channel doping profile, 177–180 small geometry effect on, 183–190 Trans-capacitances, 238 Transition capacitance, 73 Transport current, 227 Transport equations, 49 Traps, 42 Triode region, 157 Tunnel diode, 348 Tunnel FET (TFET) ambipolar behavior, 345 basic features, 344–346 basic theory, 346–355 design considerations, 355–357 scaling rule, 355 surface tunnel transistor (STT), 346

#### Index

Tunneling interband, 348–349, 349f, 360 mechanism, 348–351 width ( $\Delta\Phi$ ), 347 Zener, 348 Two-dimensional (2D) cross section of ideal MOS capacitor, 84f numerical simulation, 274 Poisson's equation, 329 Typical composition of compact models of IC technology, 2f

#### U

UCCM, *See* Unified charge control model (UCCM) Ultrathin-body (UTB) field-effecttransistors (FETs) (UTB-FETs), 313, 335 Unified charge-control model, 395 Unified charge control model (UCCM), 12 Unified drain current equation, 204–205 Unified theory, 266 Upper limit (UL) values, 294–295

#### V

Valence band (VB), 20 Variation of induced charge density, 105*f* Variation of *Q<sub>b</sub>*, *Q<sub>s</sub>*, and *Q<sub>i</sub>*, 108*f* Velocity saturation, 35–36, 175 channel, 271 Vertical cross section of intrinsic *pn*-junction, 51*f*  Very-large-scale-integrated (VLSI), 3, 54, 175, 274, 285, 371, 423 bipolar junction transistor (BJT), 371 generalized modeling approach for process variability-aware, 297f *I–V* relation, 299 risk of process variability, 309–310 Virtual node method, 365 VLSI, *See* Very-large-scale-integrated (VLSI) Voltage-controlled variable resistors, 154 Volume inversion, 328

# W

Ward–Dutton charge partition method, 239, 336, 340 Weak inversion current, 164 regime, 98 region, 5 Wentzel–Kramers–Brillouin (WKB), 348–349 Work functions of commonly used gate material, 87t Worst-case fixed corner models, 294–296 fixed corner models, 295f lower limit (LL) values, 294–295 upper limit (UL) values, 294–295

# Z

Zener breakdown, 72 Zener tunneling, 348